



MHA ZENTGRAF Ball valve Series: BKH Steel SAE420 flange PN320/350/420

Characteristics

Series: BKH

Construction type: 2-way

Housing construction: 3-part

Housing material: Steel

Material quality: Forged steel

Surface protection: Zinc Plated

Connection: SAE420 flange

Standard connection: ISO 6162-2

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Spindle material	Secondary spindle seal material	Body seal	Weight	Article
									kg	
DN13	PN350	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	1.5	14613008
DN13	PN350	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	1.5	14288321
DN13	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	1.5	14613009
DN13	PN420	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	1.5	14288324
DN20	PN350	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	3	14613012
DN20	PN350	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	3	14288432
DN20	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	3	14613013
DN20	PN420	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	3	14288437
DN25	PN320	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	4.5	14613016
DN25	PN320	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	4.5	14288298
DN25	PN350	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	4.5	14288301
DN25	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	4.5	14613017

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.