

## GATES Hydraulic hose TH8



### Characteristics

- Type:** TH8
- Material of inner wall:** Polyester
- Material of outer wall:** Polyurethane, pinpricked
- Quality cover:** Standard
- Temperature range [°C]:** -54 / 93 °C
- EN standard:** EN 855-R8
- SAE standard:** SAE 100 R8
- ISO standard:** ISO 3949 R8

### Application

- Recommended for high pressure hydraulic applications, especially material handling equipment with mast and pulley systems like forklifts, aerial lifting, hydraulic boom cranes and many others.

### Technical Information

#### Temperature range:

- -53°C to +93°C

### Construction

#### Tube:

- PA (Nylon) based.

#### Reinforcement:

- Two fibre braids.

#### Cover:

- PU (Polyurethane) based. Black TH8 is perforated for use in general hydraulic and pneumatic service.

### Approval

#### Standards:

- Exceeds ISO 3949 R8. EN 855 R8. SAE 100 R8.

### Options

#### Recommended couplings:

- MegaCrimp®

Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Article
		in	mm	bar	bar	mm		
4TH8XCT76	DN06	1/4"	15.5	350	1400	50	Black	14607010
6TH8XCT76	DN10	3/8"	19.1	280	1120	65	Black	11603933
8TH8XCT76	DN12	1/2"	22.1	245	980	100	Black	11603934
12TH8XCT61	DN19	3/4"	28.7	158	632	165	Black	14607011
16TH8XCT61	DN25	1"	36.8	140	560	250	Black	14607012

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.