



SMC Speed Exhaust Controller series ASV

Series ASV, speed exhaust controller provides an effective area that is two times larger than that of a speed controller. A silencer, one-touch fitting and flame resistant resin body is supplied as standard on the ASV. All brass parts are electroless nickel-plated.

Characteristics

Series: ASV

Temperature range: -5 / 60 °C

Operating pressure: 1 / 10 bar

Housing material: PBT

Material seal: NBR

Fitting type	Port Size in	Port Size mm	Article
Quick exhaust valve	1/8		ASV310F-01-06S
Quick exhaust valve	1/8		ASV410F-01-10S
Quick exhaust valve	1/8		ASV310F-01-08S
Quick exhaust valve	1/8		ASV410F-01-08S
Quick exhaust valve	1/4		ASV410F-02-10S
Quick exhaust valve	1/4		ASV510F-02-10S
Quick exhaust valve	1/4		ASV310F-02-08S
Quick exhaust valve	1/4		ASV510F-02-12S
Quick exhaust valve	1/4		ASV410F-02-08S
Quick exhaust valve	1/4		ASV310F-02-06S
Quick exhaust valve	3/8		ASV510F-03-10S
Quick exhaust valve	3/8		ASV410F-03-08S
Quick exhaust valve	3/8		ASV410F-03-10S
Quick exhaust valve	3/8		ASV510F-03-12S
Quick exhaust valve	1/2		ASV510F-04-12S
Quick exhaust valve	1/2		ASV510F-04-10S
Quick exhaust valve		M 5x0.8	ASV220F-M5-04
Quick exhaust valve		M 5x0.8	ASV220F-M5-06

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.