


## Cylindrical vibration damper D NR



### Characteristics

Type: D

Material rubber: NR



### Size table:

D	H	G	L
mm	mm		mm
12.5	10	M5	10
12.5	13.5	M5	10
15	15	M6	12
16	10	M5	10
16	25	M5	12
20	12	M6	20
25	15	M6	19
25.5	10	M8	20
30	15	M8	20
40	20	M10	25
50	21	M10	28

Hardness rubber	Material metal	Outside diameter	Outside height	Thread size	Article
		mm	mm		
55	Galvanized steel	12.5	10	M5	10041222
55	Galvanized steel	12.5	13.5	M5	10041223
55	Galvanized steel	15	15	M6	10041228
55	Galvanized steel	16	10	M5	10041230
55	Galvanized steel	16	25	M5	10041234
55	Galvanized steel	20	12	M6	10041235
55	Galvanized steel	25	15	M6	10041242
55	Galvanized steel	25.5	10	M8	10041249
55	Galvanized steel	30	15	M8	10041256
55	Galvanized steel	40	20	M10	10041262
55	Galvanized steel	50	21	M10	10041270

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.