


Membranegrommet CR



Membrane grommets, material CR, type DG are deliverable in 10 different dimensions for holes in metal walls of Ø15,5 upto 79mm. They are used for blocking cable outlets in switch boxes, machines and apparatus or for feeding through cables, pipes and tubes. Random diameters upto 69mm, when the membranes corresponding have been die cut. Colour: black. Hardness: 50-60 Shore A.

Indication of use

Not REACH compliant, may contain ETU CAS 96-45-7



Size table:

A	B	C	D	E
mm	mm	mm	mm	mm
11	18.5	23	7	2
13.5	20.5	25	7	2
16	22.5	27.5	7	2
21	28	35	8	2
29	37	44	9	2
36	47	54	10	2.5
48	60	68	10	2.5
53	64	75	10	2.5
69	79	90	10	2.5
9	15.5	20	7	2

Material	Overall thickness	A	B	C	D	E	Colour	Article
	mm	mm	mm	mm	mm	mm		
CR	1	11	18.5	23	7	2	Black	12731220
CR	1	13.5	20.5	25	7	2	Black	12731222
CR	1	16	22.5	27.5	7	2	Black	12731223
CR	1	21	28	35	8	2	Black	12731224
CR	1	29	37	44	9	2	Black	12731225
CR	1	36	47	54	10	2.5	Black	12731226
CR	1	48	60	68	10	2.5	Black	12731227
CR	1.5	53	64	75	10	2.5	Black	12731228
CR	1.5	69	79	90	10	2.5	Black	12731229
CR	1	9	15.5	20	7	2	Black	12731219

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.