


## PEPPERL+FUCHS Proximity switch Series: NBB2



### Characteristics

**Series:** NBB2

**Execution:** Proximity switch

**Explosion-proof:** No

**With connection cable:** Yes

**Ambient temperature:** -40 / 85 °C

Switch model	Type of switch	Switching function	Number of switches	Supply voltage	Ex-class	ATEX Zone	Electrical connection	Level of protection (IP value)	Material housing	Article
NBB2-12GM40-Z0-3G-3	Inductive	Normally open (NO)	1	5 - 60 V DC	Gc, Dc, Ex ec / Ex tc	Zone 2 / 22	PVC cable, 2 m/0.14 mm <sup>2</sup>	IP67	Brass nickel-plated, sensing face PBT	13489323
NBB2-8GS35-E2-V1	Inductive	Normally open (NO)	1	5 - 30 V DC			4-pin, M12 x 1 connector	IP67	Stainless steel 1.4305 / AISI 303, sensing face LCP	14031794
NBB2-V3-E2	Inductive	Normally open (NO)	1	10 - 30 V DC			PVC cable, 130 mm/0.14 mm <sup>2</sup>	IP67	Plastic PBT	10053860

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.