

## 80A-2 Plate wheel



### Characteristics

**Series:** Sprocket PWL

**Type:** ASA80A-2

Norm	Pitch mm	Pitch in	Number of teeth	Material	Article
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	9	Steel C45 [1.0503]	14432247
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	13	Steel C45 [1.0503]	14432341
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	14	Steel C45 [1.0503]	14432342
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	15	Steel C45 [1.0503]	14432343
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	25	Steel C45 [1.0503]	14432344
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	30	Steel C45 [1.0503]	14432345
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	32	Steel C45 [1.0503]	14432346
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	34	Steel C45 [1.0503]	14432347
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	38	Steel C45 [1.0503]	14432348
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	45	Steel C45 [1.0503]	14432349
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	48	Steel C45 [1.0503]	14432350
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	57	Steel C45 [1.0503]	14432351
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	76	Steel C45 [1.0503]	14432352
ISO 606 - DIN 8188 - ANSI B29.1	25.4	1	90	Steel C45 [1.0503]	14432353

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.