



Hose Verto, PVC suction & discharge hose to 6 bar



Characteristics

Series: Verto

Application

- Transfer of liquid food products
- Light and flexible hose for industrial and agricultural irrigation
- For pumping and suction of water, mud and other liquid products
- Phthalate free
- Free from cadmium, lead and barium

Technical Information

Temperature range

- from -10 °C till +60 °C [depending on medium]

Construction

- Transparent flexible green PVC material, reinforced with an internal, rigid, anti-shock PVC spiral reinforcement
- Smooth internal surface and corrugated external surface
- Great flexibility, even at low temperatures

Approval

- EC1935/2004 - EU 10/2011 (A,B,C)
- EC 2023/2006 GMP
- RoHS 2011/65/EU guideline
- REACH regulation EC 1907/2006

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	%	mm	m	kg/m	
19	3	25	5	15	90	60	50	0.17	10014940
25	3	31	5	15	90	75	50	0.28	10014941
32	3	38	5	15	90	96	50	0.33	10014942
35		41.4	5	15	90	105	50	0.41	11197108
38	3.2	44.4	5	15	90	120	50	0.44	10014943
40		46.4	4	12	90	120	50	0.47	11054175
45		52	4	12	90	135	50	0.57	11197109
51	3.5	58	4	12	90	150	50	0.68	10014944
55		62.6	4	12	90	165	50	0.73	11197110
60		67.6	3	9	90	180	50	0.81	11197111
63		70.6	3	9	90	195	50	0.87	10015898
70		77.6	3	9	90	210	50	0.94	11197112
76	3.3	82.6	3	9	90	228	50	1.05	10014945

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.