



Hose Vulcano, thermoplastic suction & blower hose up to 125 °C

Characteristics

Series: Vulcano

Application

- Suction of hot gases and smoke from welding and engines.
- Ventilation, heating systems, fresh air supply.

Technical Information

Temperature range

- from -40 °C till +135 °C (depending on medium)

Construction

- Black TPV thermoplastic rubber, reinforced with a special galvanised steel spiral
- Highly flexible and very light

Approval

- Flame-retardant according UL94 category HB
- RoHS 2011/65/EU guideline
- REACH regulation EC 1907/2006

Internal diameter	Wall thickness	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	bar	%	mm	m	kg/m	
228	2.6	2.6	4	185	10		11192862
279	2.8	2.8	4	230	10		11192864
40	0.4		20	32	10	0.16	11192764
51	0.5		20	40	10	0.23	11192765
60	0.5		17	50	10	0.26	11192766
63	0.5		17	55	6	0.27	11192767
70	0.5		17	60	10	0.28	11192768
76	0.6		17	65	10	0.29	11192769
80	0.6		16	65	10	0.34	11192770
90	0.6		16	75	10	0.38	11192771
102	0.6		13	85	10	0.5	11192772
110	0.65		12	90	10	0.55	11192853
120	0.65		10	100	10	0.61	11192854
127	0.65		10	105	10	0.65	11192855
130	0.75		8	105	10	0.69	11192856
140	0.75		8	115	10	0.72	11192857
152	0.75		8	125	10	0.9	11192858
160	0.75		7	130	10	0.96	11192859
180	0.8		5	150	10	1.09	11192860
203	0.8		4	165	10	1.17	11192861
254	0.8		4	210	10	1.5	11192863

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.