



Hose Delta-MD, PVC lay flat water discharge hose

Characteristics

Series: Delta

Type: MD

Application

- Flat hose to pump liquids, for agricultural irrigation and to transport water in general applications
- Striated hose for greater resistance to dragging
- Thanks to its flat structure, it is easy to use and roll up, occupying little space
- Free from cadmium, lead and barium
- Phthalate free
- Medium pressure version [other pressure ratings on demand]

Technical Information

Temperature range

- from -10 °C till +60 °C (depending on medium)

Burst pressure

- 3:1

Construction

Tube

- Smooth

Reinforcements

- High tensile strength polyester yarn

Cover

- Striated

Approval

- RoHS 2011/65/EU guideline
- REACH regulation EC 1907/2006

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Roll length	Weight	Article
mm	mm	mm	bar	bar	m	kg/m	
25	2.2	29.4	10	30	50	0.24	10014946
30	2.2		10	30	50	0.27	11195651
32	2.2	36.4	10	30	50	0.29	10015919
35	2.2		10	30	50	0.3	11195652
38	2.2	42.4	10	30	50	0.33	10014953
40	2.2		10	30	50	0.35	11195653
45	2.2		10	30	50	0.4	11195654
51	2.2	55.4	8	24	50	0.48	10014947
63	2.2	67.4	7	21	50	0.54	10014954
70	2.2		7	21	50	0.62	11195656
76	2.4	80.8	7	21	50	0.75	10014948
80	2.4		7	21	50	0.8	11195657
90	2.4		7	21	50	0.9	11195658
102	2.4	106.8	6	18	50	1.05	10014949
127	2.5	132	6	18	50	1.39	10014950
152	3	158	4	12	50	1.8	10014951
203	2.5	208	3	9	50	2	10014952

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.