



Hose Eloflex, light PVC suction & cable protection hose

Characteristics

Series: Eloflex

Application

- Suction hose for air, gases, industrial ventilation, dust, vapours, textile fibres, etc.
- Can also be used as a cable protection hose
- Light and very flexible in use
- Phthalate free

Technical Information

Temperature range

- from -15 °C till +60 °C (depending on medium)

Construction

- Flexible black PVC hose, reinforced with a white rigid PVC spiral
- Great flexibility (bending radius = internal diameter)
- Smooth internal surface and corrugated external surface
- Anti-shock PVC spiral, resistant to deformation

Approval

- Flame retardant according UL94 category V2
- RoHS 2011/65/EU guideline
- REACH regulation EC 1907/2006

Internal diameter	Wall thickness	Outer diameter	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	%	mm	m	kg/m	
19	2.4	46.8	30	19	50		12131969
40	3.2	85	30	50	50		12081263
25	2.6		50	25	50	0.17	12081250
30	2.8		50	30	50	0.21	12134668
32	3		50	32	50	0.21	12081251
35	3.1		50	35	50	0.24	12131964
38	3.1		50	38	50	0.26	12081252
45	3.5		40	45	50	0.41	12131965
50	3.5		40	50	50	0.45	12081266
60	4		40	60	50	0.54	12081267
65	4		40	65	50	0.59	12131968
70	4.2		40	70	50	0.64	12081268
75	4.5		40	75	50	0.69	12081269
80	4.8		40	80	50	0.78	12081270
90	4.5		40	90	30	0.83	12081271
102	5		40	100	30	0.98	12081272
110	5.2		40	110	30	1.15	12081283
120	5.5		40	120	30	1.2	12081284
125	5.5		40	125	30	1.25	12081285
150	6		40	150	30	1.7	12081286

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.