

DANFOSS Orbitmotor Xcel XL2 Series



Characteristics

Series: XL2
Direction of rotation: Clockwise and counterclockwise

Mounting flange	Drive shaft	Displacement cm³/r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
SAE-A 4 bolts	Cylindrical 32 mm	80	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00083A	13277215
SAE-A 4 bolts	Cylindrical 32 mm	102	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00084A	13277216
SAE-A 4 bolts	Cylindrical 32 mm	131	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00085A	13277217
SAE-A 4 bolts	Cylindrical 32 mm	157	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00086A	13249033
SAE-A 4 bolts	Cylindrical 32 mm	195	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00087A	13277218
SAE-A 4 bolts	Cylindrical 32 mm	244	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00088A	13277219
SAE-A 4 bolts	Cylindrical 32 mm	306	205	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00089A	13277220
SAE-A 4 bolts	Cylindrical 32 mm	393	155	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00090A	13277221
SAE-A 4 bolts	Cylindrical 32 mm	488	120	BSP female 1/2 "BSP	BSP female 1/2 "BSP	Side	629AG00091A	13277222

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.