



FUCHS RENOLIN CLP

Heavy duty, EP industrial gear oils with excellent extreme pressure characteristics, high load carrying capacity and good ageing stability, demulsifying

Characteristics

Series: RENOLIN

| Packaging | Volume l | Article |
|-----------|-------------|----------|
| Barrel | 60 | 14296320 |
| Barrel | 60 | 14296326 |
| Barrel | 205 | 14296319 |
| Barrel | 205 | 14296316 |
| Barrel | 205 | 14296322 |
| Barrel | 205 | 14296325 |
| Barrel | 205 | 14296336 |
| Barrel | 205 | 14296332 |
| Barrel | 205 | 13378490 |
| Bucket | 20 | 14296315 |
| Bucket | 20 | 14296318 |
| Bucket | 20 | 13457727 |
| Bucket | 20 | 14296333 |
| Bucket | 20 | 14296327 |
| Bucket | 20 | 14296321 |
| Bucket | 20 | 14296335 |
| IBC | 1000 | 14296331 |
| IBC | 1000 | 14296317 |
| IBC | 1000 | 14296328 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.