

KROHNE Vortex flowmeter Type: 8242 Series: Optiswirl 4200C

Characteristics

Series: Optiswirl 4200C

Type: 8242

Adjustable measuring range: Yes **Process connection:** Flange Pressure rating flange: PN40 Standard connection: EN 1092-1 Supply voltage: 12 - 36V DC 2 wire

Electrical connection: Cable screw gland M20 x 1,5 Degree of protection (IP) of evaluation electronic:

IP66/IP67 Display: Yes

Material measuring tube: Stainless steel 316L Process connection material: Stainless steel 316L

Material switch housing: Aluminium

Max. pressure: 40 bar

Medium temperature: -40 / 240 °C Ambient temperature: -40 / 85 °C

Application

- Flow measurement of liquids, gases and vapours.
- Measurement of saturated steam.
- Steam boiler monitoring.
- SIP and CIP processes in food, beverage and pharmaceutical industries.
- Safety-related measurement in SIL applications.

Technical Information

- Primary measured value number of separated
- Reference conditions water and air at 20 °C / 1.013
- Maximum measurement error of measured value at volume flow liquids: ± 0.75 % Re ≥ 20000; ± 2.0 % 10000 < Re < 20000.
- Maximum measurement error of measured value at volume flow gases and steam: ± 1.0 % Re ≥ 20000; ± 2.0 % 10000 < Re < 20000.
- Temperature compensation for saturated steam.
- According IEC 61508 classification SIL 2/3.

Options

- Pressure compensation for gasses or superheated steam.
- Remote version with field housing converter.
- Compact sandwich version.

Measuring range	Measuring unit	Size process connection	Output signal	Article
2 / 70	m/s	DN25	4 - 20 mA HART and pulse	14530370
2 / 80	m/s	DN40	4 - 20 mA HART and pulse	14530497
2 / 80	m/s	DN50	4 - 20 mA HART and pulse	14530496

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: valves@eriks.be

Page 1/1

PR1579278067918145_EN_26.06.2024