

SCHNEIDER Switchbox Type: 2594 Series: SGE985



Characteristics

Series: SGE985

Type: 2594

Execution: Proximity switch

Suitable for actuator: Lineaire aandrijving met kolommen

Explosion-proof: No

Cable connector: M20x1.5

With connection cable: No

With console: Yes

Standard actuator connection: DIN IEC 60534-6-1

Material konsole: Stainless steel 304

Ambient temperature: -40 / 85 °C

Application

- Feedback on opening and closing positions of pneumatically actuated linear globe valves.
- Industrial applications.

Technical Information

- Maximum stroke 100 mm.
- Including stainless steel mounting bracket for columns type EBZG-FN.

Switch model	Type of switch	Switching function	Number of switches	Supply voltage	Off-state current	Electrical connection	Level of protection [IP value]	Material housing	Article
V4NT7UL	Mechanical	Normally closed [NC]	2	Max. 50V AC/DC		Screwed terminal	IP65	Aluminium	14600598
P+F SB3.5-E2	PNP	Normally open [NO]	2	10 - 30 V DC	100 mA	Screwed terminal	IP65	Aluminium	14600752

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.