



## MHA ZENTGRAF Ball valve Series: BKH Steel SAEFS420 split flange PN320/350/420

### Characteristics

**Series:** BKH

**Construction type:** 2-way

**Housing material:** Steel

**Surface protection:** Zinc Plated

**Connection:** SAEFS420 split flange

**Standard connection:** ISO 6162-2

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 100 °C

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Spindle material	Secondary spindle seal material	Body seal	Weight kg	Article
DN13	PN350	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	0.85	14613010
DN13	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	0.9	14613011
DN20	PN350	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	1.9	14613014
DN20	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	1.9	14613015
DN25	PN320	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	2.7	14613018
DN25	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	3.7	14613019

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.