



MHA ZENTGRAF Ball valve Series: MKHP Steel SAEFS210 split flange PN210/280/420

Characteristics

Series: MKHP

Construction type: 2-way

Housing material: Steel

Surface protection: Zinc Plated

Connection: SAEFS420 split flange

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Spindle material	Secondary spindle seal material	Body seal	Weight	Article
									kg	
DN32	PN280	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	4.3	14613027
DN32	PN280	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	4.3	14613028
DN32	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	4.8	14613029
DN32	PN420	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	4.8	14613030
DN40	PN210	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	6.6	14613035
DN40	PN210	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	6.6	14613036
DN40	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	7.5	14613037
DN40	PN420	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	7.5	14613038
DN50	PN210	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	9.3	14613044
DN50	PN210	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	9.3	14613045
DN50	PN420	Manufacturer standard	Handle	Steel	POM	Steel	FPM (FKM)	FPM (FKM)	11.4	14613046
DN50	PN420	Manufacturer standard	Handle	Steel	POM	Steel	NBR	NBR	11.4	14613047

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.