



MHA ZENTGRAF Ball valve Series: MKHP420 Steel Internal thread (BSPP) PN420

Characteristics

Series: MKHP420

Construction type: 2-way

Housing material: Steel

Surface protection: Zinc Plated

Connection: Internal thread (BSPP)

Body seal: FPM (FKM)

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 100 °C

| Nominal inner diameter | Standard thread connection | Pressure rating | Face to Face norm | Manual operation | Material ball | Seat material | Spindle material | Secondary spindle seal material | Weight kg | Article |
|------------------------|----------------------------|-----------------|-----------------------|------------------|---------------|---------------|------------------|---------------------------------|--------------|----------|
| 1.1/4" [32] | ISO 228-1 | PN420 | Manufacturer standard | Handle | Steel | POM | Steel | FPM (FKM) | 3.5 | 14612977 |
| 1.1/2" [40] | ISO 228-1 | PN420 | Manufacturer standard | Handle | Steel | POM | Steel | FPM (FKM) | 5.7 | 14612986 |
| 2" [50] | ISO 228-1 | PN420 | Manufacturer standard | Handle | Steel | POM | Steel | FPM (FKM) | 8.2 | 14612991 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.