

MHA ZENTGRAF Ball valve Series: MKHP420 Steel Cutting ring, light (L) PN420



Characteristics

Series: MKHP420
Construction type: 2-way
Housing material: Steel
Surface protection: Zinc Plated
Connection: Cutting ring, light (L)
Standard connection: DIN 2353 / ISO 8434-1
Seat material: POM

Characteristics (2)

Spindle material: Steel
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Material ball	Secondary spindle seal material	Body seal	Weight	Article
	mm								mm	
DN32	35	M 45x2	PN420	Manufacturer standard	Handle	Steel	FPM (FKM)	FPM (FKM)	3.5	14612973
DN32	35	M 45x2	PN420	Manufacturer standard	Handle	Steel	NBR	NBR	3.5	14612974
DN40	42	M 52x2	PN420	Manufacturer standard	Handle	Steel	FPM (FKM)	FPM (FKM)	5.7	14612984
DN40	42	M 52x2	PN420	Manufacturer standard	Handle	Steel	NBR	NBR	5.7	14612985

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.