

GATES Hydraulic hose EFG4K-XTF (R12) XtraTuff™

Characteristics

Type: EFG4K-XTF

Material of inner wall: NBR

Material of outer wall: CR

Quality cover: Gates XtraTuff

Temperature range [°C]: -40 / 121 °C

EN standard: EN 856-R12

SAE standard: SAE 100 R12

ISO standard: ISO 3862 R12

Application

- Extremely high pressure and high impulse hydraulic applications.

Technical Information

Temperature range:

- 40°C to +121°C

Construction

Tube:

- NBR (Nitrile) based.

Reinforcement:

- Four alternating layers of spiralled, high tensile steel wire.

Cover:

- CR (Chloroprene) based.
- MSHA approved.
- XtraTuff™

Execution

- 40% of EN 856 4SP bend radius at rated working pressure.
- Most flexible EN 856 R12 / SAE 100R12 hose in the industry.
- Superior flex impulse performance: tested to 1,000,000 impulse cycles at 50% of EN 856 R12 and SAE 100R12 bend radii.
- EFG4K-XTF hose is compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids.
- Gates special XtraTuff hose cover offers 25 times the abrasion resistance of the standard EFG4K cover as per ISO 6945.

Approval

Standards:

- Exceeds ISO 3862 R12. EN 856 R12. SAE 100 R12.
- Meets or exceeds performance requirements of EN 856 4SP [-16, -20].

Type approval:

- DNV

Options

Recommended couplings:

- GlobalSpiral™



Code	Hose ID (DN)	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Article
		in	mm	bar	bar	mm		
6EFG4K-XTFXLL	DN10	3/8"	20.3	280	1120	65	Black	14606960
8EFG4K-XTFXLL	DN12	1/2"	23.9	280	1120	90	Black	14606961
10EFG4K-XTFXLL	DN16	5/8"	27.7	280	1120	100	Black	14606962
12EFG4K-XTFXLL	DN19	3/4"	30.7	280	1120	120	Black	14606963
16EFG4K-XTFXLL	DN25	1"	38.1	280	1120	150	Black	14606964
20EFG4K-XTFXLL	DN31	1.1/4"	47	280	1120	210	Black	14606965

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.