

## Hose shank brass with male thread type 1VH - flat seal



### Characteristics

**Type of component:** Hose tail coupling

**Material:** Brass

**Connection type:** Threaded coupling

**Hose fitting type:** Male thread

**Connection termination:** NPT

**Elbow angle [degr.]:** 45 °

**Hose tail execution:** Serrated

**Temperature range [°C]:** -20 / 65 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/8		10	145	13193528
1/4"	DN06	6	87	10038956
1/8"	DN06	6	87	10038957
1/2"	DN06	6	87	10038955
3/8"	DN06	6	87	10038958
3/8"	DN08	6	87	10038964
1/8"	DN08	6	87	10038963
1/4"	DN08	6	87	10038962
1/2"	DN08	6	87	12183676
1/4"	DN10	6	87	10038930
1/2"	DN10	6	87	10038929
3/8"	DN10	6	87	10038931
1/2"	DN12	6	87	10038933
1/4"	DN12	6	87	10038935
3/4"	DN12	6	87	10038936
3/8"	DN12	6	87	10038937
1/2"	DN16	6	87	10038939
3/4"	DN16	6	87	11304606
1/2"	DN19	6	87	10038942
3/4"	DN19	6	87	10038940
1"	DN19	6	87	10038941
1"	DN25	6	87	10038946
3/4"	DN25	6	87	11092700
1.1/4"	DN32	6	87	10038949
2"	DN38	6	87	10070455
1.1/2"	DN38	6	87	10038951
1.1/2"	DN50	6	87	11304609
2.1/2"	DN63	6	87	10038960
3"	DN75	6	87	10038961
4"	DN100	6	87	11171144
3"	DN80	6	87	11171143

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.