

GATES Hydraulic hose MXT (R16)

Characteristics

Type: MXT

Material of inner wall: NBR

Material of outer wall: NBR/PVC

Quality cover: Standard

Temperature range [°C]: -40 / 100 °C

SAE standard: SAE 100 R16

ISO standard: ISO 11237 R16

Application

- Recommended for high-pressure hydraulic applications.
- Easy to route and to install in tight areas.

Technical Information

Temperature range:

- -40°C to +100°C

Construction

Tube:

- NBR (Nitrile) based.

Reinforcement:

- Braided high-tensile steel wire.

Cover:

- NBR/PVC based.
- MSHA approved.

Execution

- Superior flex impulse performance: tested to 600,000 impulse cycles, which is 3 times the impulse criteria.
- Lower force-to-bend for faster and more ergonomic installation.
- Lightweight for easier handling and reduced equipment weight.
- MXT hose is compatible with biodegradable hydraulic fluids like synthetic esters, polyglycols and vegetable oils as well as petroleum-based fluids.
- Patented construction.

Approval

Standards:

- Exceeds SAE 100R 16, ISO 11237 R16 and ISO 11237 R17 [-4 to -12].
- Exceeds EN 853 2SN and EN 857 2SC performance.
- Exceeds ISO 1436 R2 and ISO 11237 R19 [-4 to -8] performance.

Options

Recommended couplings:

- MegaCrimp®

Code	Hose ID [DN]	Hose ID	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Outside wall colour	Weight	Article
		in							
4MXTXRL175	DN06	1/4"	14.2	420	1680	40	Black	0.3	13628661
4MXTXBALE	DN06	1/4"	14.2	420	1680	40	Black	0.3	13628670
5MXTXBALE	DN08	5/16"	15.2	380	1520	45	Black	0.33	13628671
5MXTXRL150	DN08	5/16"	15.2	380	1520	45	Black	0.33	13628663
6MXTXBALE	DN10	3/8"	17.3	330	1320	65	Black	0.39	13628672
6MXTXRL100	DN10	3/8"	17.3	330	1320	65	Black	0.39	13628665
8MXTXRL75	DN12	1/2"	20.3	280	1120	70	Black	0.46	13628666
8MXTXBALE	DN12	1/2"	20.3	280	1120	70	Black	0.46	13628673
10MXTXBALE	DN16	5/8"	24.1	250	1000	75	Black	0.57	13628674
10MXTXRL50	DN16	5/8"	24.1	250	1000	75	Black	0.57	13628667
12MXTXRL50	DN19	3/4"	27.4	215	860	120	Black	0.7	13628668
12MXTXBALE	DN19	3/4"	27.4	215	860	120	Black	0.7	13628675
16MXTXBALE	DN25	1"	35.1	165	660	150	Black	1	13628676
16MXTXRL30	DN25	1"	35.1	165	660	150	Black	1	13628669

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.