



WEG 3 Phase motor W21 Aluminium B14T (6P)

The W21 Multimounting has aluminum frame and removable feet being able to provide great flexibility and facilitate the change of configuration without requiring additional machining or modifications. Its terminal box can rotate every 90 degrees, allowing the connection of the motor cables on any side. Furthermore, these motors are totally interchangeable with the cast iron motors.

Characteristics

Series: W21

Type: B14T

Speed: 1000 rpm

Mounting: B14T

Number of poles: 6

Full load speed: 970 rpm

Full load torque: 1.239 Nm

Nominal rated frequency: 50 Hz

Material: Aluminium

PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Flange diameter (outside diameter) mm	Article
IE2	0.12	230/400	63	11	90	12552119
IE2	0.18	230/400	71	14	105	12552124
IE2	0.25	230/400	71	14	105	12552129
IE2	0.37	230/400	80	19	120	12552134
IE2	0.55	230/400	80	19	120	12552139
IE3	0.12	230/400	63	11	90	13024284
IE3	0.12	230/400	63	11	90	13313335
IE3	0.18	230/400	71	14	105	13024297
IE3	0.18	230/400	71	14	105	13313355
IE3	0.25	230/400	71	14	105	13024304
IE3	0.25	230/400	71	14	105	13313377
IE3	0.25	230/400	71			13332342
IE3	0.37	230/400	80	19	120	13024311
IE3	0.37	230/400	80	19	120	13313395
IE3	0.55	230/400	80	19	120	13024318
IE3	0.55	230/400	80	19	120	13313413
IE3	0.75	230/400	90S/L	24	140	13024326
IE3	1.1	230/400	100L	28	160	13024340
IE3	1.5	230/400	100L	28	160	13024354
IE3	2.2	230/400	112M	28	160	13411136
IE3	2.2	400/690	112M	28	160	13024368
IE3	3	230/400	132S	38	200	13411156
IE3	3	400/690	132S	38	200	13024380
IE3	4	400/690	132M	38	200	13024394

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.