




SISTO Diaphragm valve Type: 5651 Cast iron Flange PN10

Characteristics

Type: 5651
Norm: EN (DIN)
Housing construction: KB (Straight through type)
Housing material: Cast iron
Material quality: EN-JL1040
Surface protection: Manufacturer standard
Connection: Flange

Characteristics [2]

Flange finish: Raised face
Face to Face norm: EN 558, Series 1
Manual operation: Hand wheel, rising with rising stem
With position indicator: Yes



Membrane material	Nominal inner diameter	Pressure rating	Face to Face length	Material bonnet	Actuator material	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Maximum pressure difference at 20 °C	Article
			mm			°C	°C	bar	
IIR (butyl)	DN25	PN10	160	EN-JL1040	Steel	-10	120	10	11813783
IIR (butyl)	DN32	PN10	180	EN-JL1040	Steel	-10	120	10	11813784
IIR (butyl)	DN40	PN10	200	EN-JL1040	Steel	-10	120	10	11813785
IIR (butyl)	DN80	PN10	310	EN-JL1040	Steel	-10	120	10	11813788
IIR (butyl)	DN100	PN10	350	EN-JL1040	Steel	-10	120	10	11813789
IIR (butyl)	DN150	PN10	480	EN-JL1040	Steel	-10	120	10	11813790

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.