


Float valve Type: 730 Float material: Stainless steel External thread (BSPP)




Characteristics

Type: 730
Norm: EN (DIN)
Housing material: Stainless steel
Material quality: 1.4301
Connection: External thread (BSPP)
Connection 2: Internal thread (BSPP)
Pressure rating: PN4
Face to Face norm: Manufacturer standard
Sealing: PTFE

Characteristics (2)

Material floating rod: 1.4301
Minimum medium temperature (continuous): -10 °C
Maximum medium temperature (continuous): 185 °C
Maximum pressure difference at 20 °C: 4 bar



Thread connection ["]	L [mm]	L1 mm	Weight [kg]	Float Ø [mm]
3/8	405	445	1,4	120
1/2	430	506	1,6	150
3/4	440	495	2,1	220
1	532	597	3,3	240
1,25	520	597	4,2	240
1,5	538	617	5,4	260
2	575	669	8	300

Max. oper. pressure	Temp.
4 Bar.	185°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.