



## TA Regulating valve Series: STAG Type: 26223 Static Ductile cast iron Groove

### Characteristics

**Series:** STAG

**Type:** 26223

**Housing material:** Ductile cast iron

**Material quality:** EN-JS1030

**Surface protection:** Coated

**Connection:** Groove

**Type of control gear:** Static


**Application:** CH water

**With measuring nipples:** Yes

**Material disc:** AMETAL

**Spindle material:** AMETAL

**Material bonnet:** EN-JL1040



**Nipple material:** Brass

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 120 °C

**With position indicator:** Yes

### Application

- Recommended in: Utilities

Nominal inner diameter	Outer pipe diameter mm	Pressure rating	Control range l/h	Kvs value m <sup>3</sup> /h	Kv value m <sup>3</sup> /h	Sealing	Article
DN65	76.1	Class 150	1800 / 85000	85	1.8 / 85	EPDM	13389189
DN80	88.9	Class 150	2000 / 120000	190	2 / 120	EPDM	13389188
DN100	114.3	Class 150	2500 / 190000	190	2.5 / 190	EPDM	13389183
DN125	139.7	PN16	5500 / 300000	300	5.5 / 300	EPDM	13389187
DN150	168.3	Class 150	6500 / 420000	420	6.5 / 420	EPDM	13389184
DN200	219.1	Class 150	40000 / 765000	765	40 / 765	EPDM	13389186
DN250	273	Class 150	90000 / 1185000	1185	90 / 1185	EPDM	13389185

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.