



FENNER V-pulley for taper bush section SPB - 8 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: B/SPB/QXPB

Number of grooves: 8

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
54	51	54
53.5	51	53.5
46.5	65	46.5
47	65	47
41	76	41
35	89	35
28	102	28

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
160	3020	3	Cast iron	16.1	54	51	54	11422065
170	3020	3	Cast iron	16.1	54	51	54	11422073
180	3020	3	Cast iron	16.1	53.5	51	53.5	11422080
190	3020	3	Cast iron	16.1	53.5	51	53.5	11422088
200	3525	3	Cast iron	16.1	46.5	65	46.5	11422096
212	3525	3	Cast iron	16.1	46.5	65	46.5	11422103
224	3525	3	Cast iron	16.1	46.5	65	46.5	11422111
236	3525	3	Cast iron	16.1	46.5	65	46.5	11422118
250	3525	3	Cast iron	16.1	46.5	65	46.5	11422125
300	3525	7	Cast iron	16.1	47	65	47	11422140
315	3525	7	Cast iron	16.1	46.5	65	46.5	11422146
335	3525	7	Cast iron	16.1	47	65	47	11422153
355	3525	7	Cast iron	16.1	46.5	65	46.5	11422160
400	3525	5	Cast iron	16.1	46.5	65	46.5	11422167
450	3525	5	Cast iron	16.1	46.5	65	46.5	11422181
500	3525	5	Cast iron	16.1	46.5	65	46.5	11422187
560	4030		Cast iron	16.1				11422195
630	4030	5	Cast iron	16.1	41	76	41	11422201
710	4535	5	Cast iron	16.1	35	89	35	11422353
900	4535	5	Cast iron	16.1	35	89	35	11459841
1000	5040		Cast iron	16.1				11422220
1250	5040	5	Cast iron	16.1	28	102	28	11422227

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.