



FENNER V-pulley for taper bush section SPZ - 4 grooves

Fenner® Taper Lock® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: Z/SPZ/QXPZ

Number of grooves: 4

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
27	25	
27	25	0
	32	20
	45	
3.5	45	3.5

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
85	1610	6	Cast iron	9.7	27	25		11421702
90	1610		Cast iron	9.7				11421707
95	1610	6	Cast iron	9.7	27	25		11421711
100	1610		Cast iron	9.7	27	25	0	11421717
112	2012		Cast iron	9.7				11421729
118	2012		Cast iron	9.7				11421735
125	2012	2	Cast iron	9.7		32	20	11421742
132	2012		Cast iron	9.7				11421749
140	2012		Cast iron	9.7				11421755
150	2517	2	Cast iron	9.7		45		11421761
160	2517		Cast iron	9.7				11421767
170	2517		Cast iron	9.7				11421773
180	2517		Cast iron	9.7				11421778
190	2517	7	Cast iron	9.7	3.5	45	3.5	11422344
200	2517		Cast iron	9.7				11421785
224	2517		Cast iron	9.7				11421791
250	2517		Cast iron	9.7				11421797
315	2517		Cast iron	9.7				11421809
355	2517		Cast iron	9.7				11421815
450	3020		Cast iron	9.7				11421822

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.