



ASCO Pilot valve 3/2 fig. 33404 series 327 stainless steel



Characteristics

Series: 327
Type: 33404
Model: Pilot valve 3/2 way
Function: Universal
Actuation: Direct-acting
Electrical connection: Plug EN 175301-803 type A
Including plug: Yes
Max. viscosity: 65 mm²/s
Minimum pressure difference: 0 bar
Maximum pressure difference: 10 bar
Housing material: Stainless steel
Material quality: 1.4404

Characteristics [2]

Material coil housing: Epoxy
Material shorting ring: Silver
Working time: 100 %
Level of protection (IP value): IP65
Emergency manual operation: No
Explosion-proof: No
SIL certified: Yes
Approvals: SIL

| Process connection | Size process connection | Connection air exhaust[s] | Coil type | Supply voltage | Frequency | Power | Starting power | Orifice mm | Kvs value m ³ /h | Article |
|------------------------|-------------------------|---------------------------|----------------|----------------|-----------|----------------------------|----------------|------------|-----------------------------|----------|
| Internal thread [BSPP] | 1/2" [15] | 1/2" [15] | SPC 400923-342 | 24V DC | | 9 W [hot] / 10 W [cold] | | 12 | 1.5 | 12427365 |
| Internal thread [BSPP] | 1/4" [8] | 1/4" [8] | SPC 400923-042 | 24V DC | | 3.2 W [hot] / 3.6 W [cold] | | 5.7 | 0.45 | 12427346 |
| Internal thread [BSPP] | 1/4" [8] | 1/4" [8] | SPC 400425-142 | 24V DC | | 9 W [hot] - 11.2 W [cold] | | 5.7 | 0.45 | 11883188 |
| Internal thread [BSPP] | 1/4" [8] | 1/4" [8] | SPC 400923-342 | 24V DC | | 9 W [hot] / 10 W [cold] | | 12 | 1.5 | 12427364 |
| Internal thread [BSPP] | 1/4" [8] | 1/4" [8] | SPC 123664-017 | 230V AC | 50/60Hz | 10 W | 10 VA | 5.7 | 0.45 | 11520179 |
| Internal thread [NPT] | 1/4" [8] | 1/4" [8] | SPC 400923-042 | 24V DC | | 3.2 W [hot] / 3.6 W [cold] | | 5.7 | 0.45 | 12427348 |
| Internal thread [NPT] | 1/4" [8] | 1/4" [8] | SPC 400425-142 | 24V DC | | 9 W [hot] - 11.2 W [cold] | | 5.7 | 0.45 | 11396539 |
| Internal thread [NPT] | 1/4" [8] | 1/4" [8] | SPC 400923-342 | 24V DC | | 9 W [hot] / 10 W [cold] | | 12 | 1.5 | 12427368 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.