



## GF Reducer in PVDF Serie: 908 PN16 Plastic welded end

### Characteristics

**Series:** 908

**Material:** PVDF

**Connection:** Plastic welded end

**Suited for electrofusion fitting:** No

**Minimum medium temperature (continuous):** -20 °C

**Maximum medium temperature (continuous):** 140 °C

Shape	External tube diameter of connection mm	External tube diameter of connection 2 mm	Pressure rating	Article
Reduction piece	25	20	PN16	11248045
Reduction piece	32	25	PN16	11071592
Reduction piece	32	20	PN16	11065012
Reduction piece	40	20	PN16	11016581
Reduction piece	63	32	PN16	11065010
Reduction piece	63	50	PN16	11245377
Reduction piece	63	40	PN16	11016549
Reduction piece	75	40	PN16	11268002
Reduction piece	90	63	PN16	11245490
Reduction piece	90	75	PN16	11296422
Reduction piece	110	75	PN16	11106653
Reduction piece	110	90	PN16	11248050
Reduction piece	110	63	PN16	11354329

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.