



ROSEMOUNT Pressure transmitter in line series 2051T ATEX external thread

Characteristics

Series: 2051T

Type: 2051T

Pressure unit: bar

Measuring element: Capacitive

Type of diaphragm: Inner lying

With display: No

Process connection material: Stainless steel 316L

Material sensor: Stainless steel 316L

Max. pressure: 51 bar

Level of protection (IP value): IP66/IP68

Explosion-proof: Yes

Ex-class: II 1/2G Ex db IIC Ga/Gb T6/T5/T4 - II 1G Ex ia IIC T4 Ga

Approvals: ATEX IECEx

Medium temperature: From -40 to [120 °C - T4] [80 °C - T5] [70 °C - T6] °C

Ambient temperature: From -40 to [80 °C - T4/T5] [70 °C - T6] °C

Application

- Recommended in: Chemical

Measuring range	Accuracy class	Output signal	Connection	Size process connection	Standard thread connection	Supply voltage	Electrical connection	Housing material	Max. pressure bar	Article
-1 / 2.1	0.065 %	4 - 20 mA HART	External thread [BSPP]	1/2" [15]	EN 837 - DIN 16288	10.5 - 42.4V DC	Cable entry M20 x 1.5	Aluminium	51	13561084
-1 / 2.1	0.065 %	4 - 20 mA HART	External thread [BSPP]	1/2" [15]	EN 837 - DIN 16288	10.5 - 42.4V DC	Cable entry M20 x 1.5	Stainless steel CF8M	51	13561085
-1 / 10	0.065 %	4 - 20 mA HART	External thread [BSPP]	1/2" [15]	EN 837 - DIN 16288	10.5 - 42.4V DC	Cable entry M20 x 1.5	Aluminium	103	13561088
-1 / 10	0.065 %	4 - 20 mA HART	External thread [BSPP]	1/2" [15]	EN 837 - DIN 16288	10.5 - 42.4V DC	Cable entry M20 x 1.5	Stainless steel CF8M	103	13561089
-1 / 55	0.065 %	4 - 20 mA HART	External thread [BSPP]	1/2" [15]	EN 837 - DIN 16288	10.5 - 42.4V DC	Cable entry M20 x 1.5	Aluminium	110	13561092
-1 / 55	0.065 %	4 - 20 mA HART	External thread [BSPP]	1/2" [15]	EN 837 - DIN 16288	10.5 - 42.4V DC	Cable entry M20 x 1.5	Stainless steel CF8M	110	13561093

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.