

WALVOIL 2SP-A group 2, flange: B50CY (60x60 mm), tapered shaft 11: 1:5 M12, T connections: flange D

Characteristics

Mounting flange: German (60x60 mm) ø 50 mm

Drive shaft: German tapered 1:5 (M12) Execution (single/tandem): Single

Type: External Gear Pump Positition oil ports: Side Seal material: NBR Shaft seal type: Standard

Displacement cm³/r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Code	Article
4	Clockwise	250	German flanged port	s German flanged ports: 35/15/M6	2SP-A-040-D-B50CY-B- N-11-0-T	13339581
4	Counterclockwise	250	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-040-S-B50CY-B- N-11-0-T	13339591
6	Clockwise	250	German flanged port 40/20/M6	s German flanged ports: 35/15/M6	2SP-A-060-D-B50CY-B- N-11-0-T	13339582
6	Counterclockwise	250	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-060-S-B50CY-B- N-11-0-T	13339592
11	Clockwise	250	40/20/M6	s German flanged ports 35/15/M6	N-11-0-T	13339584
11	Counterclockwise	250	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-110-S-B50CY-B- N-11-0-T	13339594
14	Clockwise	250	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-140-D-B50CY-B- N-11-0-T	13339585
14	Counterclockwise	250	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-140-S-B50CY-B- N-11-0-T	13339595
26	Clockwise	170	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-260-D-B50CY-B- N-11-0-T	13339589
26	Counterclockwise	170	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-260-S-B50CY-B- N-11-0-T	13339599
8,5	Clockwise	250	40/20/M6	s German flanged ports: 35/15/M6	N-11-0-T	13339583
8,5	Counterclockwise	250	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-080-S-B50CY-B- N-11-0-T	13339593
16,5	Clockwise	230	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-160-D-B50CY-B- N-11-0-T	13339586
16,5	Counterclockwise	230	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-160-S-B50CY-B- N-11-0-T	13339596
19,5	Clockwise	210	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-190-D-B50CY-B- N-11-0-T	13339587
19,5	Counterclockwise	210	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-190-S-B50CY-B- N-11-0-T	13339597
22,5	Clockwise	190	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-220-D-B50CY-B- N-11-0-T	13339588
22,5	Counterclockwise	190	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-220-S-B50CY-B- N-11-0-T	13339598
31,5	Clockwise	130	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-310-D-B50CY-B- N-11-0-T	13339590
31,5	Counterclockwise	130	German flanged port 40/20/M6	s German flanged ports 35/15/M6	2SP-A-310-S-B50CY-B- N-11-0-T	13339600

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR3158022664738204_EN_03.07.2024

ERIKS BV