



WALVOIL 2SP-A group 2, flange: B80C (100x72 mm), toothed shaft 16: DIN B17x14 9t short, N connections: flange

Characteristics

Mounting flange: German (100x72 mm) ø 80 mm

Drive shaft: Spline B 17x14xe9 DIN 5482

Execution (single/tandem): Single

Type: External Gear Pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Options	Code	Article
4	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	Short shaft	2SP-A-040-D-B80C-B-N-16-0-N	13339431
4	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	Short shaft	2SP-A-040-S-B80C-B-N-16-0-N	13339441
6	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	Short shaft	2SP-A-060-D-B80C-B-N-16-0-N	13339432
6	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	Short shaft	2SP-A-060-S-B80C-B-N-16-0-N	13339442
11	Clockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-110-D-B80C-B-N-16-0-N	13339434
11	Counterclockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-110-S-B80C-B-N-16-0-N	13339444
14	Clockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-140-D-B80C-B-N-16-0-N	13339435
14	Counterclockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-140-S-B80C-B-N-16-0-N	13339445
26	Clockwise	170	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-260-D-B80C-B-N-16-0-N	13339439
26	Counterclockwise	170	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-260-S-B80C-B-N-16-0-N	13339449
8,5	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	Short shaft	2SP-A-080-D-B80C-B-N-16-0-N	13339433
8,5	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	Short shaft	2SP-A-080-S-B80C-B-N-16-0-N	13339443
16,5	Clockwise	230	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-160-D-B80C-B-N-16-0-N	13339436
16,5	Counterclockwise	230	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-160-S-B80C-B-N-16-0-N	13339446
19,5	Clockwise	210	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-190-D-B80C-B-N-16-0-N	13339437
19,5	Counterclockwise	210	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-190-S-B80C-B-N-16-0-N	13339447
22,5	Clockwise	190	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-220-D-B80C-B-N-16-0-N	13339438
22,5	Counterclockwise	190	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-220-S-B80C-B-N-16-0-N	13339448
31,5	Clockwise	130	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-310-D-B80C-B-N-16-0-N	13339440
31,5	Counterclockwise	130	European flanged ports 40/19/M8	European flanged ports 30/13/M6	Short shaft	2SP-A-310-S-B80C-B-N-16-0-N	13339450

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.