



BURKERT Solenoid valve 2/2 Type: 32350 series 6213EV brass internal thread

Characteristics

Series: 6213EV

Type: 32350

Function: Normally closed [NC]

Actuation: Pilot operated hung diaphragm

Electrical connection: Plug EN 175301-803 type A

Max. viscosity: 21 mm²/s

Housing material: Brass

Material quality: CW617N [CuZn40Pb2]

Sealing: NBR

Material coil housing: PA

Material shorting ring: Copper

Membrane material: NBR

Working time: 100 %

Level of protection (IP value): IP65

Emergency manual operation: None

Explosion-proof: No

Medium temperature: From -10 °C to 80 °C

Ambient temperature: From 0 °C to 55 °C

Application


- Neutral liquids such as water and light oil.

Technical Information

- Water hammer damping.
- Without plug.

Options

- Available with KTW/W270 and NEN-EN-IEC60730-2-8 stamp.



Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Article
		mm	m ³ /h	bar	bar					
1.1/2" (40)	Internal thread (BSPP)	40	30	0.5	10	SPC 35181	24V AC	16 W / 37 VA	150 VA	13340245
1.1/2" (40)	Internal thread (BSPP)	40	30	0.5	10	SPC 35182	24V DC	21 W [hot] - 28 W [cold]		13340244
1.1/2" (40)	Internal thread (BSPP)	40	30	0.5	10	SPC 35181	230V AC	16 W / 37 VA	150 VA	13340246
1.1/4" (32)	Internal thread (BSPP)	25	11	0.5	10	SPC 35181	24V AC	16 W / 37 VA	150 VA	13340242
1.1/4" (32)	Internal thread (BSPP)	25	11	0.5	10	SPC 35182	24V DC	21 W [hot] - 28 W [cold]		13340241
1.1/4" (32)	Internal thread (BSPP)	25	11	0.5	10	SPC 35181	230V AC	16 W / 37 VA	150 VA	13340243
1/2" (15)	Internal thread (BSPP)	10	1.9	0.5	10	SPC 35160	24V AC	8 W / 14 VA	34 VA	13340224
1/2" (15)	Internal thread (BSPP)	10	1.9	0.5	10	SPC 35163	24V DC	10 W [hot] - 11 W [cold]		13340223
1/2" (15)	Internal thread (BSPP)	10	1.9	0.5	10	SPC 35160	230V AC	8 W / 14 VA	34 VA	13340225
1/2" (15)	Internal thread (BSPP)	13	3.6	0.5	10	SPC 35160	24V AC	8 W / 14 VA	36 VA	13340227
1/2" (15)	Internal thread (BSPP)	13	3.6	0.5	10	SPC 35163	24V DC	10 W [hot] - 11 W [cold]		13340226
1/2" (15)	Internal thread (BSPP)	13	3.6	0.5	10	SPC 35160	230V AC	8 W / 14 VA	36 VA	13340228
1" (25)	Internal thread (BSPP)	20	8.3	0.5	10	SPC 35160	24V AC	8 W / 14 VA	38 VA	13340236
1" (25)	Internal thread (BSPP)	20	8.3	0.5	10	SPC 35163	24V DC	10 W [hot] - 11 W [cold]		13340235
1" (25)	Internal thread (BSPP)	20	8.3	0.5	10	SPC 35160	230V AC	8 W / 14 VA	38 VA	13340237
1" (25)	Internal thread (BSPP)	25	11	0.5	10	SPC 35181	24V AC	16 W / 37 VA	150 VA	13340239
1" (25)	Internal thread (BSPP)	25	11	0.5	10	SPC 35182	24V DC	21 W [hot] - 28 W [cold]		13340238
1" (25)	Internal thread (BSPP)	25	11	0.5	10	SPC 35181	230V AC	16 W / 37 VA	150 VA	13340240
1/4" (8)	Internal thread (BSPP)	10	1.3	0.5	10	SPC 35160	24V AC	8 W / 14 VA	34 VA	13340218

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Article
		mm	m ³ /h	bar	bar					
1/4" (8)	Internal thread (BSPP)	10	1.3	0.5	10	SPC 35163	24V DC	10 W (hot) - 11 W (cold)		13332712
1/4" (8)	Internal thread (BSPP)	10	1.3	0.5	10	SPC 35160	230V AC	8 W / 14 VA	34 VA	13340219
2" (50)	Internal thread (BSPP)	40	30	0.5	10	SPC 35181	24V AC	16 W / 37 VA	150 VA	13340248
2" (50)	Internal thread (BSPP)	40	30	0.5	10	SPC 35182	24V DC	21 W (hot) - 28 W (cold)		13340247
2" (50)	Internal thread (BSPP)	40	30	0.5	10	SPC 35181	230V AC	16 W / 37 VA	150 VA	13340249
3/4" (20)	Internal thread (BSPP)	13	3.6	0.5	10	SPC 35160	24V AC	8 W / 14 VA	36 VA	13340230
3/4" (20)	Internal thread (BSPP)	13	3.6	0.5	10	SPC 35163	24V DC	10 W (hot) - 11 W (cold)		13340229
3/4" (20)	Internal thread (BSPP)	13	3.6	0.5	10	SPC 35160	230V AC	8 W / 14 VA	36 VA	13340231
3/4" (20)	Internal thread (BSPP)	20	8.3	0.5	10	SPC 35160	24V AC	8 W / 14 VA	38 VA	13340233
3/4" (20)	Internal thread (BSPP)	20	8.3	0.5	10	SPC 35163	24V DC	10 W (hot) - 11 W (cold)		13340232
3/4" (20)	Internal thread (BSPP)	20	8.3	0.5	10	SPC 35160	230V AC	8 W / 14 VA	38 VA	13340234
3/8" (10)	Internal thread (BSPP)	10	1.9	0.5	10	SPC 35160	24V AC	8 W / 14 VA	34 VA	13340221
3/8" (10)	Internal thread (BSPP)	10	1.9	0.5	10	SPC 35163	24V DC	10 W (hot) - 11 W (cold)		13340220
3/8" (10)	Internal thread (BSPP)	10	1.9	0.5	10	SPC 35160	230V AC	8 W / 14 VA	34 VA	13340222

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.