


ECON® Stem extension Type: 8007 Stainless steel Suitable for: ISO 5211 Direct Mount

Characteristics

- Type: 8007
- Material: Stainless steel
- Material quality: 1.4308
- Valve stem shape: Square
- Actuator stem shape: Square



Size	H [mm]	E [mm]	F [mm]	nxO1 [mm]	nxO2 [mm]	ISO5211 N1/N2
1	100	9	9	4x6	4x6	F03/F04
2	100	9	9	4x6	4x7	F03/F05
3	100	11	11	4x6	4x7	F04/F05
4	100	11	11	4x6	4x9	F04/F07
5	100	14	14	4x7	4x9	F05/F07
6	100	17	17	4x9	4x11	F07/F10
7	100	22	22		4x11	F10
8	120	27	27		4x14	F12
9	120	27	27	4x14	4x18	F12/F14

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Valve mounting flange	Size valve stem mm	Actuator mounting flange	Height mm	Article
F04	9	F03/F04	100	12304212
F05	11	F04/F05	100	12360295
F05	9	F03/F05	100	12267728
F07	11	F04/F07	100	12744174
F07	14	F05/F07	100	12125475
F10	22	F10	100	12115150
F10	17	F07/F10	100	12125441
F12	27	F12	120	12360294
F14	36	F14	120	14463315

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.