

KEMPER Globe valve Series: 190 02 Type: 2409KB Bronze KIWA Internal thread (BSPP) PN16

Characteristics

Series: 190 02
Type: 2409KB
Construction type: Free-flow
Housing material: Bronze
Connection: Internal thread (BSPP)
KIWA: Yes

Application


- Heating and cooling systems
- Industrial applications.
- Installation technology
- Recommended in: Utilities

Technical Information

- The metal parts that come into contact with the medium are made of dezincification-resistant, non-corroding bronze and are resistant to aggressive water.
- Maintenance-free spindle seal with self-lubricating EPDM lip seal, exchangeable under pressure
- Rotatable cone, protected against pressure impulses
- With drain stop
- With mounting option for the Pt1000 temperature sensor
- Spindle wire outside the medium
- EPDM seat
- With black handwheel
- No dead space

Approval

- DVGW, ÖVGW, SVGW, WRAS, KIWA and VA CERTIFICATES
- Plastic parts with KTW and W270 certificates



Material quality	Nominal inner diameter	Pressure rating	Operation	Type of disc	Type of bonnet	Sealing	Article
CC499K	1/2" [15]	PN16	Hand wheel	Fixed disc	Screwed	EPDM	13427478
CC499K	3/4" [20]	PN16	Hand wheel	Fixed disc	Screwed	EPDM	12954122
CC499K	1" [25]	PN16	Hand wheel	Fixed disc	Screwed	EPDM	13427479
CC499K	1.1/4" [32]	PN16	Hand wheel	Fixed disc	Screwed	EPDM	13427480
CC499K	1.1/2" [40]	PN16	Hand wheel	Fixed disc	Screwed	EPDM	13427481
CC499K	2" [50]	PN16	Hand wheel	Fixed disc	Screwed	EPDM	13410563

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.