




ASCO Solenoid valve 2/2 Type: 32018 series 262-263K-LT brass cryogenic internal thread

Characteristics

Series: 262-263K-LT
Type: 32018
Function: Normally closed (NC)
Actuation: Direct-acting
Minimum pressure difference: 0 bar
Electrical connection: Plug EN 175301-803 type A
Max. viscosity: 65 mm²/s
Housing material: Brass
Sealing: PTFE
Material coil housing: Epoxy

Characteristics [2]

Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP65
Emergency manual operation: None
Explosion-proof: No
SIL certified: No



Conn. ["]	Coil type	Power	A [mm]	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight [kg]	
1/8	SPC	35030	~ 55 / 23 VA	86	50	30	48	45	68	83	100	0,7
1/8	SPC	35030	<td>≥ 11,2 Watt	86	50	30	48	45	68	83	100	0,7
1/4	SPC	35031	~ 78 / 35 VA	86	50	30	48	45	68	83	100	0,7
1/4	SPC	35030	<td>≥ 11,2 Watt	86	50	30	48	45	68	83	100	0,7
1/4	SPC	35030	~ 55 / 23 VA	86	50	30	48	45	68	83	100	0,7
3/8	SPC	35031	~ 78 / 35 VA	86	50	30	48	45	68	83	100	0,7
3/8	SPC	35030	<td>≥ 11,2 Watt	86	50	30	48	45	68	83	100	0,7
3/8	SPC	35030	~ 55 / 23 VA	86	50	30	48	45	68	83	100	0,7

Conn. ["]	Orifice [mm]	Coil type	dP Min. [bar]	Max. differential pressure		Cryogenic liquids	
				Air/gas [=DC]	[~AC]	[=DC]	[~AC]
1/8	3,2	SPC 35030	0	5	9	5	9
1/4	5,6	SPC 35030	0	2	-	2	-
1/4	5,6	SPC 35031	0	-	7	-	7
1/4	7,1	SPC 35030	0	1	3	1	3
3/8	5,6	SPC 35030	0	2	7	2	7

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Conn.	Orifice	Coil type	dP Min.	Max. differential pressure		Cryogenic liquids
				Air/gas		
3/8	7,1	SPC 35030	0	1	3	1 3
Medium temperature: -196° C tot 90°C						
Ambient temperature: -20° C tot 75 en 50°C with coil type SPC 35031						

Size process connection	Process connection	Orifice	Kvs value	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Medium temperature	Article
		mm	m³/h	bar						
1/4" [8]	Internal thread (BSPP)	5.6	0.63	6.9	238613-106	24V AC	17.1 W / 40 VA	70 VA	From -196 °C to 60°C	13448297
1/4" [8]	Internal thread (NPT)	5.6	0.63	2.9	238913-106	24V DC	8.5 W [hot] - 11.6 W [cold]		From -196 °C to 60°C	13448298
1/4" [8]	Internal thread (BSPP)	7.1	0.6	3	SPC 35030	24V AC	10.5 W	55 VA	From -196 °C to 90°C	11815098
1/4" [8]	Internal thread (BSPP)	7.1	0.6	3	SPC 35030	230V AC	10.5 W	55 VA	From -196 °C to 90°C	11815101
1/8" [6]	Internal thread (BSPP)	3.2	0.3	10.7	238613-059	230V AC	10.1 W / 25 VA	50 VA	From -196 °C to 60°C	13448323
3/8" [10]	Internal thread (BSPP)	5.6	0.63	6.2	238613-106	24V AC	17.1 W / 40 VA	70 VA	From -196 °C to 60°C	13706495
3/8" [10]	Internal thread (BSPP)	5.6	0.63	2.9	238913-106	24V DC	8.5 W [hot] - 11.6 W [cold]		From -196 °C to 60°C	13448301
3/8" [10]	Internal thread (BSPP)	5.6	0.63	6.2	238613-159	230V AC	17.1 W / 40 VA	70 VA	From -196 °C to 60°C	13448302
3/8" [10]	Internal thread (BSPP)	7.1	0.76	4	238613-106	24V AC	17.1 W / 40 VA	70 VA	From -196 °C to 60°C	13448299
3/8" [10]	Internal thread (BSPP)	7.1	0.76	4	238613-159	230V AC	17.1 W / 40 VA	70 VA	From -196 °C to 60°C	13448300

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.