

GOODALL Hosetail DuraCrimp Male Thread BSP cone 60°



Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: BSPT

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 260 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/4"	DN06	160	2320	13253802
3/8"	DN10	160	2320	13253803
1/2"	DN10	160	2.32	13581785
1/2"	DN12	160	2320	13253804
1/2"	DN16	160	2320	13253805
3/4"	DN20	160	2320	13253806
1"	DN25	160	2320	13253807
1"	DN20	160	2.32	13580746
1/4"	DN06	160	2320	13224802
3/8"	DN10	160	2320	13224803
1/2"	DN12	160	2320	13224804
1/2"	DN16	160	2320	13224805
3/4"	DN20	160	2320	13224806
1"	DN25	160	2320	13224807
1.1/4"	DN32	100	1450	13224808
1.1/2"	DN38	100	1450	13224809
2"	DN50	100	1450	13224810

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.