

GOODALL Hosetail DuraCrimp Male Thread NPT



Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: NPT

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 260 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/4"	DN06	160	2320	13253820
3/8"	DN10	160	2320	13253821
1/2"	DN12	160	2320	13253822
1/2"	DN16	160	2.32	13253823
3/4"	DN20	160	2320	13253824
1"	DN25	160	2320	13253825
1.1/4"	DN32	160	2320	13253826
1.1/2"	DN38	125	1812	13253827
1/4"	DN06	160	2320	13224820
3/8"	DN10	160	2320	13224821
1/2"	DN12	160	2320	13224822
1/2"	DN16	160	2.32	13224823
1"	DN20	160	2.32	14071275
3/4"	DN20	160	2320	13224824
1"	DN25	160	2320	13224825
1.1/4"	DN32	100	1450	13224826
1.1/2"	DN38	100	1450	13224827
2"	DN50	100	1450	13224828

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.