



## OLEODINAMICA MARCHESINI 2 ways flow divider V-EQ

These valves are used when two equal actuators, that are not mechanically couples, supplied by the same pump and controlled by a single valve, must move simultaneously both in extension and retraction.

Material:

- Body: zinc-plated steel.
- Internal parts: hardened and ground steel.
- Seals: BUNA N.

Mounting:

- Pipemounting: BSP ports.

### Characteristics

**Type:** Inline mounting

**Max. operating pressure:** 250 bar



| Volume flow<br>l/min | Connections               | Material  | Article  |
|----------------------|---------------------------|-----------|----------|
| 1-3                  | C,A,B: 3/8" BSP           | Cast iron | 12495718 |
| 3-6                  | C,A,B: 3/8" BSP           | Cast iron | 12495719 |
| 6-10                 | C,A,B: 3/8" BSP           | Cast iron | 12495720 |
| 10-20                | C,A,B: 3/8" BSP           | Cast iron | 12495721 |
| 20-32                | C,A,B: 3/8" BSP           | Cast iron | 12495722 |
| 25-40                | C: 1/2"BSP, A,B: 3/8" BSP | Cast iron | 12495723 |
| 40-60                | C: 1/2"BSP, A,B: 3/8" BSP | Cast iron | 12495724 |
| 60-80                | C: 1/2"BSP, A,B: 3/8" BSP | Cast iron | 12495725 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.