



## FESTO Basic valve CPE18

### Characteristics

**Series:** CPE18

**Operation:** Via pilot interface to ISO 15218

**Operating temperature:** -5 / 50 °C

**Fluid:** Compressed air in accordance with ISO8573-1:2010 [7:4:4]

Flow rate at 6 Bar l/min	Port thread type	Port Size in	Operating pressure bar	Function	Pilot supply	Construction size	Housing material	Seal material	Article
1.2	BSPP (G)	1/4	-0.9 / 10	5/3 exhausted	External	8	Aluminium die-cast	NBR	12263871
1.2	BSPP (G)	1/4	2.5 / 10	5/3 exhausted	Internal	8	Aluminium die-cast	NBR	14163881
1.3	BSPP (G)	1/4	-0.9 / 10	3/2 closed, monostable	External	8	Aluminium die-cast	NBR	14163493
1.3	BSPP (G)	1/4	2.5 / 10	3/2 closed, monostable	Internal	8	Aluminium die-cast	NBR	14163492
1.3	BSPP (G)	1/4	-0.9 / 10	5/3 pressurized	External	8	Aluminium die-cast	NBR	14163884
1.3	BSPP (G)	1/4	2.5 / 10	5/3 pressurized	Internal	8	Aluminium die-cast	NBR	14163882
1.45	BSPP (G)	1/4	-0.9 / 10	5/3 closed	External	8	Aluminium die-cast	NBR	14163880
1.45	BSPP (G)	1/4	2.5 / 10	5/3 closed	Internal	8	Aluminium die-cast	NBR	14163878
1.5	BSPP (G)	1/4	-0.9 / 10	5/2 Bistable	External	8	Aluminium die-cast	NBR	14163632
1.5	BSPP (G)	1/4	2 / 10	5/2 Bistable	Internal	8	Aluminium die-cast	NBR	12263870
1.5	BSPP (G)	1/4	-0.9 / 10	5/2 monostable	External	8	Aluminium die-cast	NBR	14163631
1.5	BSPP (G)	1/4	2.5 / 10	5/2 monostable	Internal	8	Aluminium die-cast	NBR	12263869
1.7	BSPP (G)	1/4	-0.9 / 10	3/2 open, monostable	External	8	Aluminium die-cast	NBR	14163494
1.7	BSPP (G)	1/4	2.5 / 10	3/2 open, monostable	Internal	8	Aluminium die-cast	NBR	12263872

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.