



FESTO Basic valve VZWE

Characteristics

Series: VZWE

Operation: Electrical

Operating temperature: -10 / 80 °C

Operating pressure bar	Function	Construction size	Protection class	Housing material	Seal material	Article
0 / 4	2/2 closed, monostable	40	IP65	Aluminium die-cast	NBR	14163053
0.35 / 8	2/2 closed, monostable	25	IP65	Aluminium die-cast	NBR	14163051
0.35 / 8	2/2 closed, monostable	62	IP65	Aluminium die-cast	NBR	14163057
0.35 / 8	2/2 closed, monostable	50	IP65	Aluminium die-cast	NBR	14163055
0.35 / 8	2/2 closed, monostable	20	IP65	Aluminium die-cast	NBR	13213124
0.35 / 8	2/2 closed, monostable	50	IP65	Aluminium die-cast	NBR	14163054
0.35 / 8	2/2 closed, monostable	62	IP65	Aluminium die-cast	NBR	14163056
0.35 / 8	2/2 closed, monostable	76	IP65	Aluminium die-cast	NBR	14163058
0.35 / 8	2/2 closed, monostable	40	IP65	Aluminium die-cast	NBR	14163052
0.35 / 8	2/2 closed, monostable	25	IP65	Aluminium die-cast	NBR	14163050

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.