



FESTO Three-Point gripper HGDD

Characteristics

Series: HGDD

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
HGDD-35-A-G2	35	Double acting	4	M5			4 / 8	14167290
HGDD-35-A-G1	35	Double acting	4	M5			4 / 8	14167293
HGDD-35-A	35	Double acting	4	M5	336	366	3 / 8	14171686
HGDD-40-A-G1	40	Double acting	6	M5			4 / 8	14167300
HGDD-40-A	40	Double acting	6	M5	600	648	3 / 8	14171687
HGDD-40-A-G2	40	Double acting	6	M5			4 / 8	14167296
HGDD-50-A-G2	50	Double acting	8	G1/8			4 / 8	14167303
HGDD-50-A-G1	50	Double acting	8	G1/8			4 / 8	14167306
HGDD-50-A	50	Double acting	8	G1/8	1044	1113	3 / 8	12652125
HGDD-63-A-G2	63	Double acting	10	G1/8			4 / 8	14167311
HGDD-63-A	63	Double acting	10	G1/8	1659	1746	3 / 8	14171688
HGDD-63-A-G1	63	Double acting	10	G1/8			4 / 8	14167315
HGDD-80-A-G1	80	Double acting	12	G1/8			4 / 8	14167322
HGDD-80-A-G2	80	Double acting	12	G1/8			4 / 8	14167318
HGDD-80-A	80	Double acting	12	G1/8	2745	2829	3 / 8	14171689

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.