



FESTO Rotary indexing table DHTG

Characteristics

Series: DHTG

Operation: Double acting

Cushioning: Shock absorber, adjustable

Housing material: Aluminium alloy

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Ambient temperature: 5 / 60 °C

Operating pressure: 4 / 8 bar

Sound pressure level: < = 70 dB(A)

Manufacturer ID	Construction size	Pitch	Port Size	Theoretical torque at 6 bar	Article
			in	Nm	
DHTG-65-2-A	65	2	M5	2.1	11650544
DHTG-65-3-A	65	3	M5	2.1	12264676
DHTG-65-4-A	65	4	M5	2.1	11650545
DHTG-65-6-A	65	6	M5	2.1	11650546
DHTG-65-8-A	65	8	M5	2.1	11650547
DHTG-65-12-A	65	12	M5	2.1	11650548
DHTG-65-24-A	65	24	M5	2.1	11650549
DHTG-90-2-A	90	2	M5	4.4	11650550
DHTG-90-3-A	90	3	M5	4.4	11651214
DHTG-90-4-A	90	4	M5	4.4	11650551
DHTG-90-6-A	90	6	M5	4.4	11650552
DHTG-90-8-A	90	8	M5	4.4	11650553
DHTG-90-12-A	90	12	M5	4.4	11650554
DHTG-90-24-A	90	24	M5	4.4	11650555
DHTG-140-3-A	140	3	1/8	18.1	11651215
DHTG-140-4-A	140	4	1/8	18.1	11650556
DHTG-140-6-A	140	6	1/8	18.1	11650557
DHTG-140-8-A	140	8	1/8	18.1	11650558
DHTG-140-12-A	140	12	1/8	18.1	11650559
DHTG-140-24-A	140	24	1/8	18.1	11650560
DHTG-220-3-A	220	3	1/8	58.9	11651216
DHTG-220-4-A	220	4	1/8	58.9	11650561
DHTG-220-6-A	220	6	1/8	58.9	11650562
DHTG-220-8-A	220	8	1/8	58.9	11650563
DHTG-220-12-A	220	12	1/8	58.9	11650564
DHTG-220-24-A	220	24	1/8	58.9	11650565

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.