



FESTO Mini slide SLS

Characteristics

Series: SLS

Function: Double acting

Housing material: Aluminium alloy

Operating temperature: -20 / 60 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	mm	bar	
SLS-6-5-P-A	Mechanical	6	5	M 5	1.5 / 10	11633367
SLS-6-10-P-A	Mechanical	6	10	M 5	1.5 / 10	11633368
SLS-6-15-P-A	Mechanical	6	15	M 5	1.5 / 10	11633369
SLS-6-20-P-A	Mechanical	6	20	M 5	1.5 / 10	11633370
SLS-6-25-P-A	Mechanical	6	25	M 5	1.5 / 10	11633371
SLS-6-30-P-A	Mechanical	6	30	M 5	1.5 / 10	23211810
SLS-10-5-P-A	Mechanical	10	5	M 5	1 / 10	11633372
SLS-10-10-P-A	Mechanical	10	10	M 5	1 / 10	11633373
SLS-10-15-P-A	Mechanical	10	15	M 5	1 / 10	11633374
SLS-10-20-P-A	Mechanical	10	20	M 5	1 / 10	11633375
SLS-10-25-P-A	Mechanical	10	25	M 5	1 / 10	11633376
SLS-10-30-P-A	Mechanical	10	30	M 5	1 / 10	23211811
SLS-16-5-P-A	Mechanical	16	5	M 5	1 / 10	11633377
SLS-16-10-P-A	Mechanical	16	10	M 5	1 / 10	11633378
SLS-16-15-P-A	Mechanical	16	15	M 5	1 / 10	11633379
SLS-16-20-P-A	Mechanical	16	20	M 5	1 / 10	11633380
SLS-16-25-P-A	Mechanical	16	25	M 5	1 / 10	11633381
SLS-16-30-P-A	Mechanical	16	30	M 5	1 / 10	11633382

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.