



FESTO Barbed fitting CRCN

Characteristics

Series: CRCN

Operating temperature: 0 / 60 °C

Operating pressure: 0.95 / 10 bar

Manufacturer ID	Material	Connection 1	Connection 2	Nominal size mm	Wrench width mm	Article
CRCN-M5-PK-2	High alloy steel, non-corrosive	Tubing O.D. 3mm	M5	7	7	11627865
CRCN-1/8-PK-3	High alloy steel, non-corrosive	Tubing O.D. 4mm	1/8" BSPP[G]	13	13	11627152
CRCN-M5-PK-3	High alloy steel, non-corrosive	Tubing O.D. 4mm	M5	7	7	11627150
CRCN-1/4-PK-4	High alloy steel, non-corrosive	Tubing O.D. 6mm	1/4" BSPP[G]	17	17	11627155
CRCN-1/8-PK-4	High alloy steel, non-corrosive	Tubing O.D. 6mm	1/8" BSPP[G]	13	13	11627153
CRCN-M5-PK-4	High alloy steel, non-corrosive	Tubing O.D. 6mm	M5	7	7	11627151
CRCN-1/4-PK-6	High alloy steel, non-corrosive	Tubing O.D. 8mm	1/4" BSPP[G]	17	17	11627156
CRCN-1/8-PK-6	High alloy steel, non-corrosive	Tubing O.D. 8mm	1/8" BSPP[G]	13	13	11627154
CRCN-3/8-PK-6	High alloy steel, non-corrosive	Tubing O.D. 8mm	3/8" BSPP[G]	19	19	11627157

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.