



FESTO Pneumatic valve J

Characteristics

Series: J

Operation: Pneumatic

Operating temperature: -5 / 50 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Norm: ISO 5599/1

Flow rate at 6 Bar l/min	Port thread type	Operating pressure bar	Function	Pilot supply	Construction size	Housing material	Seal material	Article
1		-0.9 / 10	5/2 Bistable	External	8	Aluminium die-cast	NBR	11647593
1.2		-0.9 / 16	5/2 Bistable		8	Aluminium die-cast	NBR	23212071
1.2		-0.9 / 16	5/2 Bistable		8	Aluminium die-cast	NBR	11647564
1.6		-0.9 / 10	5/2 Bistable	External	10	Aluminium die-cast	NBR	23209943
1.6		-0.9 / 10	5/2 Bistable	External	10	Aluminium die-cast	NBR	11647594
2		-0.9 / 10	5/2 Bistable	External	12	Aluminium die-cast	NBR	23212072
2		-0.9 / 10	5/2 Bistable	External	12	Aluminium die-cast	NBR	11647595
2.3		-0.9 / 16	5/2 Bistable		11.5	Aluminium die-cast	NBR	11630095
2.3		-0.9 / 16	5/2 Bistable		11.5	Aluminium die-cast	NBR	11647565
4.5		-0.9 / 16	5/2 Bistable		14.5	Aluminium die-cast	NBR	23211046
4.5		-0.9 / 16	5/2 Bistable		14.5	Aluminium die-cast	NBR	11647566
6		-0.9 / 16	5/2 Bistable		18	Aluminium	NBR	11627082
100	PK-3	-0.9 / 8	3/2 bistable		2.5	Zinc die-casting	NBR	23209940
105	PK-3	1 / 8	5/2 Bistable		2.5	Zinc die-casting	NBR	23209941
650		-0.9 / 10	5/2 Bistable	External	5	Aluminium die-cast	NBR	23211434
700		-0.9 / 10	5/2 Bistable	External	5	Aluminium die-cast	NBR	11633793
800		-0.9 / 10	5/2 Bistable	External	8	Aluminium die-cast	NBR	23209942

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.