



FESTO Toothed belt axis ELGR

Characteristics

Series: ELGR

Operating temperature: -10 / 50 °C

Degree of protection (IP): 20

Construction size	Stroke length	Repetition accuracy	Max. feed force Fx	Article
	mm	mm	N	
35	100	±0.1	50	14170343
35	200	±0.1	50	14170344
35	300	±0.1	50	14170345
35	400	±0.1	50	14170346
35	500	±0.1	50	14170349
35	600	±0.1	50	14170352
45	100	±0.1	100	14170348
45	200	±0.1	100	14170354
45	300	±0.1	100	14170357
45	400	±0.1	100	14170360
45	500	±0.1	100	14170362
45	600	±0.1	100	14170365
45	800	±0.1	100	14170370
45	1000	±0.1	100	14170374
55	100	±0.1	350	14170366
55	200	±0.1	350	14170369
55	300	±0.1	350	14170373
55	400	±0.1	350	14170376
55	500	±0.1	350	14170378
55	600	±0.1	350	14170381
55	800	±0.1	350	14170384
55	1000	±0.1	350	14170387
55	1200	±0.1	350	14170390
55	1500	±0.1	350	14170393

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.