



FESTO Gear unit EMGC

Characteristics

Series: EMGC

Gear unit type: Right-angle gear unit

Operation temperature: -25 / 90 °C

Degree of protection (IP): IP54

Gear unit flange size mm	Motor flange size mm	Gear ratio	Max. input speed 1/min	Output Torque Nm	Max. output torque Nm	Torsional resistance Nm/arcmin	Article
40	67	3:1	6000	5	10	0.85	14170462
40	67	4:1	6000	6.5	13	0.85	14170461
40	67	5:1	6000	6.5	13	0.85	14170460
40	67	7:1	6000	6.5	13	0.65	14170459
40	67	12:1	6000	10	12.5	0.85	14170468
40	67	16:1	6000	14	17.5	0.85	14170467
40	67	20:1	6000	14	17.5	0.85	14170466
40	67	25:1	6000	14	17.5	0.85	14170465
40	67	35:1	6000	14	17.5	0.85	14170464
60	67	3:1	6000	20	36	2.4	14170471
60	67	4:1	6000	26	44	2.4	14170470
60	67	5:1	6000	26	44	2.4	13383086
60	67	7:1	6000	26	44	1.7	14170469
60	67	10:1	6000	16	24	1.3	14170485
60	67	12:1	6000	36	45	2.4	14170484
60	67	16:1	6000	42	52	2.4	14170483
60	67	20:1	6000	42	52	2.4	14170482
60	67	25:1	6000	44	55	2.4	14170481
60	67	35:1	6000	44	55	2.4	14170479
60	67	40:1	6000	42	52	2.4	14170478
67	67	1:1	4500	2	2.1	0.105	14170473

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.