



FESTO Non-Return valve HB

Characteristics

Series: HB

Mounting: Threaded

Operating pressure: -1 / 10 bar

Operating temperature: 0 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:-:-]

Fitting type	Design form	Material	Tube Outside Diameter	Thread type	Thread size	Flow Rate (6 bar - delta p = 1 bar) NI/min	Article
Check valve	Compact	Anodised aluminium	10	External thread BSPT (R)	3/8	1700	11630357
Check valve	Compact	Anodised aluminium	12	External thread BSPT (R)	1/2	2206	11630361
Check valve	Compact	Anodised aluminium	12	External thread BSPT (R)	3/8	1886	11630359
Check valve	Compact	Brass, Nickel-plated	4	External thread BSPT (R)	1/8	142	23211237
Check valve	Compact	Brass, Nickel-plated	4	Outer thread metric	M5	144	11630353
Check valve	Compact	Brass, Nickel-plated	6	External thread BSPT (R)	1/4	294	11630355
Check valve	Compact	Brass, Nickel-plated	6	External thread BSPT (R)	1/8	335	11630354
Check valve	Compact	Brass, Nickel-plated	8	External thread BSPT (R)	1/4	696	23209893
Check valve	Compact	Brass, Nickel-plated	8	External thread BSPT (R)	1/8	314	11630356

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.